



India

MAXIFY GX5070



Print

▼

Print Head / Ink

Number of Nozzles

Total 4,352 nozzles

Ink Bottles

GI-76 (Pigment Black / Pigment Cyan / Pigment Magenta / Pigment Yellow)
MC-G01 (Maintenance Cartridge)

Maximum Printing Resolution

600 (horizontal)^{*1} x 1,200 (vertical) dpi

Print Speed*2

Based on ISO/IEC 24734
Click [here](#) for summary report
Click [here](#) for Document Print and Copy Speed
Measurement Conditions

Document (ESAT/Simplex)	Approx. 24.0 images per minute (black) / 15.5 images per minute (colour)
-------------------------	--

Document (ESAT/Duplex)	Approx. 13.0 images per minute (black) / 10.0 images per minute (colour)
------------------------	--

Document (FPOT Ready / Simplex)	Approx. 7s (black) / 8s (colour)
---------------------------------	----------------------------------

Printable Width	Up to 206 mm
-----------------	--------------

Printable Area

Bordered Printing	#10 Envelope, DL Envelope, Envelopes [C5, Monarch]: Top/Bottom margin: 12.7 mm, Left/Right margin: 5.6 mm 10.16x15.24cm (4x6in), 12.7x17.78cm (5x7in), 17.78x25.4cm (7x10in), 20.32x25.4cm (8x10in): Top margin: 3 mm, Bottom: 5 mm, Left/Right: 3.4 mm Square (127 x 127 mm (5 x 5in)): Top/Bottom/Left/Right margin: 6 mm Others: Top/Bottom/Left/Right margin: 5 mm
-------------------	--

Bordered Auto 2-Sided Printing

Top/Bottom/Left/Right margin: 5 mm

Supported Media

Rear Tray

Plain Paper (64 - 105 g/m²)
Photo Paper Pro Luster (LU-101)
Photo Paper Plus Glossy II (PP-201)
Matte Photo Paper (MP-101)
Double-Sided Matte Paper (MP-101D)
Glossy Photo Paper "Everyday Use" (GP-508)
High Resolution Paper (HR-101N)
Photo Paper Plus Semi-Gloss (SG-201)
Photo Stickers (PS-108/PS-208/PS-808)
Removable Photo Stickers (PS-308R)
Magnetic Photo Paper (PS-508)
Light Fabric Iron-On Transfers (LF-101)
Envelope

Cassette

Plain Paper (64 - 105 g/m²)

Paper Size

Rear Tray

A4, A5, A6, B5, LTR, LGL, B-Oficio, M-Oficio, Foolscap, FS, Executive, Envelope [#10, DL, C5, Monarch], 10.16x15.24cm (4x6in), 12.7x17.78cm (5x7in), 17.78x25.4cm (7x10in), 20.32x25.4cm (8x10in), Square 127 x 127 mm (5 x 5in)

[Custom Size]
Width 89 - 216 mm, Length 127 - 1,200 mm

Cassette

A4, A5, B5, LTR

[Custom Size]
Width 148 - 216 mm, Length 210 - 297 mm

Paper Handling (Maximum Number)

Rear Tray	Plain Paper (A4/LTR, 64 g/m²): 100 High Resolution Paper (HR-101N): 80 Photo Paper Pro Luster (LU-101, 10.16x15.24cm (4 x 6in)): 20 Photo Paper Plus Glossy II (PP-201, 10.16x15.24cm (4 x 6in)): 20 Matte Photo Paper (MP-101, 10.16x15.24cm (4 x 6in)): 20 Double-Sided Matte Paper (MP-101D, 10.16x15.24cm (4 x 6in)): 20 Glossy Photo Paper "Everyday Use" (GP-508, 10.16x15.24cm (4 x 6in)): 20 Photo Paper Plus Semi-Gloss (SG-201, 10.16x15.24cm (4 x 6in)): 20 Photo Stickers (PS-108/PS-208/PS-808): 1 Removable Photo Stickers (PS-308R): 1 Magnetic Photo Paper (PS-508): 1
-----------	--

Cassette	Plain Paper (A4/LTR, 64 g/m²): 250
----------	------------------------------------

Support Media for Auto 2-Sided Printing

Type	Plain Paper
------	-------------

Size	A4, LTR
------	---------

Paper Weight

Rear TrayPlain Paper: 64 - 105 g/m²)Canon Paper: Max. paper weight,
approx. 275 g/m²

(Photo Paper Plus Glossy II, PP-201)

CassettePlain Paper: 64 - 105 g/m²

Ink End Sensor

Electrode type and dot count type combined

Print Head Alignment

Auto / Manual

Network



Protocol

SNMP, HTTP, TCP/IP (IPv4/IPv6)

Wired LAN

Network Type

IEEE802.3u (100BASE-TX) / IEEE802.3 (10BASE-T)

Data Rate

100 Mbps / 10 Mbps (auto switchable)

Wireless LAN

Network Type

IEEE802.11b/g/n

2.4 GHz Channel: 1 - 11

US/TW/LTN/BR/CAN

2.4 GHz Channel: 1 - 13

KR/EUR/AU/ASA/CN/EMBU

Security

WPA-PSK (TKIP / AES)

WPA2-PSK (TKIP / AES)

WPA-EAP (AES)^{*3}
WPA2-EAP (AES)^{*3}

Direct Connection (Wireless LAN)	Available
----------------------------------	-----------

Printing Solutions

▼

AirPrint	Available
----------	-----------

Mopria	Available
--------	-----------

Canon Print Service (for Android)	Available
--------------------------------------	-----------

MAXIFY Cloud Link (from smartphone/tablet)	Available
---	-----------

Canon PRINT	Available
-------------	-----------

System Requirements^{*4}

▼

Windows 10 / 8.1 / 7 SP1
(operation can only be guaranteed on a PC with a pre-
installed Windows 7 or later.)

macOS 10.13.6 ~ 11

Chrome OS

General Specifications

▼

Operation Panel

Display	5.08cm LCD Display
Language	32 Languages Selectable: Japanese, English (mm & inch), French, German, Italian, Spanish, Portuguese, Dutch, Danish, Norwegian, Swedish, Finnish, Greek, Polish, Czech, Russian, Hungarian, Slovene, Turkish, Simplified Chinese, Traditional Chinese, Korean, Indonesian, Slovakian, Estonian, Latvian, Lithuanian, Ukrainian, Romanian, Bulgarian, Croatian, Vietnamese
Interface	USB 2.0
Operating Environment^{*5}	
Temperature	5 - 35°C
Humidity	10 - 90% RH (no dew condensation)
Recommended Environment^{*6}	
Temperature	15 - 30°C
Humidity	10 - 80% RH (no dew condensation)
Storage Environment	
Temperature	0 - 40°C
Humidity	5 - 95% RH (no dew condensation)
Quiet Mode	Available

Acoustic Noise (PC Print) (Approx.)

Plain Paper (A4, B/W) ^{*7}	49.0 dB(A)
-------------------------------------	------------

Power	AC 100 - 240 V, 50/60 Hz
-------	--------------------------

Power Consumption (Approx.)

OFF	0.2 W
-----	-------

Standby	0.8 W
USB connection to PC	

Printing ^{*8}	20 W
USB connection to PC	

Duty Cycle	Up to 45 000 prints/month
------------	---------------------------

Dimension (WxDxH) (Approx.)

Factory Configuration	399 x 416 x 238 mm
-----------------------	--------------------

Output Extended	399 x 639 x 332 mm
-----------------	--------------------

Weight (Approx.)	9.0 kg
------------------	--------

Page Yield

▼

Plain Paper (A4 pages) (ISO/IEC 24712 test file) ^{*9}	Standard: GI-76 PGBK: 6,000 GI-76 PG C/M/Y: 14,000
---	--

Economy: *10

GI-76 PGBK: 9,000

GI-76 PG C/M/Y: 21,000

-
1. Ink droplets can be placed with a pitch of 0.000529 cm at minimum (1/4800 in) at minimum.
 2. Document print speeds are the average of ESAT (Word, Excel, PDF) in Office Category Test for the default simplex mode, ISO/IEC 24734.
Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer.
Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.
 3. IEEE802.1X (EAP-TLS/EAP-TTLS/PEAP) available.
 4. Please visit <https://asia.canon> to check OS compatibility and to download the latest driver updates.
 5. The performance of the printer may be reduced under certain temperature and humidity conditions.
 6. For the temperature and humidity conditions of papers such as photo paper, refer to the paper's packaging or the supplied instructions.
 7. Acoustic Noise is measured based on ISO7779 standard with default setting.
 8. Print: When printing ISO/JIS-SCID N2 on A4 size plain paper using default settings.
 9. The page yield is based on the consumption data from the succeeding ink bottle but not the first ink bottle.
Colour document page yield is the estimated value based on Canon individual test method using the ISO/IEC 24712 color chart and continuous printing simulation with the replacement after initial setup.
 10. The economy mode reduces the ink consumption by lowering the density. 50% more pages can be printed by using this mode.
 11. Print yield (A4 size) is the estimate value based on Canon individual test method using test chart ISO/IEC 24712 under ideal print conditions and continuous printing simulation with the replacement set of ink bottle. Mentioned print yield is from the replacement set of 4 ink bottles (C/M/Y/BK) and not from the set of ink bottles provided inside the Printer box along with the Printer

The page yield (A4 size) is based on the consumption data from the succeeding ink bottle but not the first ink bottle. Page yield is the estimated value based on Canon individual test method using the ISO/IEC 24712 chart under ideal print conditions & continuous printing simulation with the replacement after initial setup. Mentioned print yield is from the replacement set of 4-ink bottles (C/M/Y/BK). Black bottle contains 170ml ink and each colour bottle contains 135ml of ink. Page yield varies significantly depending on contents printed and other factors.

- Prices, specifications, availability and terms of offers may change without notice.
- Products / Services may be manufactured by and/or supplied to us by third party manufacturers / suppliers for distribution / resale (non-Canon brand products).

- Prices above are maximum retail price (MRP) and may change without prior notice.
-
-

Copyright © 2025 Canon India Pvt Ltd. All rights reserved.